


## Micro Fiberoptic Probes Dip/Absorption/Transflectance



### DESCRIPTION

RoMack's dip style absorption probes, truly represent a significant leap forward in fiberoptic probe design and quality control. Responding to the needs of the widely varying requirements for scientists and process or quality control engineers, RoMack has produced a very versatile and robust series of probes.

These probes, having a diameter of 1/8" (3.17mm) provide a convenient way to perform absorption or transmission measurements in very restricted locations by dipping or inserting the probe end into the medium or environment.

World class inspection and control tools guarantee that all probes meet or exceed specifications every time and

each probe is subjected to a twelve point inspection process. Whenever possible RoMack will specifically test each probe in the environment in which they are intended to be used.

RoMack further assures the quality of all probes by issuance of a certificate of conformance and transmission vs wavelength curves for each and every probe shipped.

### INTERFACING NOTE:

Most of RoMack's probes can be used as direct plug-and-play accessories for existing fiberoptic systems currently in use.

**RoMack Probes -  
"Better by Design."**

### APPLICATIONS

- Absorption or Transflectance for use in:
  - Automated well-plate systems
  - Pharmaceutical dissolution
  - On-line process control
  - Laboratory dip spectroscopy
  - Medical

### FEATURES

- Smallest probe diameter in the industry.
- Highest throughput for its size.
- Robust design that minimizes stray light.
- Transmission data with every probe.
- Every seal checked.
- Superior design minimizes bubbles and trapped liquid.
- Industry standard or custom terminations.
- Custom configurations and instrument or process interfaces available.
- UV/VIS and VIS/NIR versions.
- Custom configurations available.

# Micro Fiberoptic Probes Dip/Absorption/Transflectance

## ORDERING/SPECIFYING INFORMATION NOTES

- Micro probe products can be ordered using the specifying system represented on this page.
- If you have any trouble with the specifying system or have any special requirements not accommodated or shown, please contact a RoMack sales associate.
- Probes are often used in harsh environments so if you have any questions about the applicability of a probe for your environment please speak to a RoMack applications engineer or sales associate.

The diagram illustrates the components and dimensions of a micro fiberoptic probe. It shows a connector (C) leading to a breakout length (BOL) section, followed by a fiber section with diameter (D) and fiber size (B). The probe length (PL) is the section at the end, ending in a path length (E) section.

<p><b>(A) Fiber Type</b></p> <ol style="list-style-type: none"> <li>1) Silica/Silica (UV/VIS)</li> <li>2) Silica/Silica Low Solarization (UV)</li> <li>3) Silica/Silica (VIS/NIR)</li> <li>4) Polymer Clad Silica(UV/VIS High NA)</li> <li>5) Polymer Clad Silica(VIS/NIR High NA)</li> <li>6) Other _____</li> </ol>	<p><b>(B) Fiber Size</b></p> <ol style="list-style-type: none"> <li>1) 100µm</li> <li>2) 200µm</li> <li>3) 300µm</li> <li>4) 400µm</li> <li>5) Other _____</li> </ol>	<p><b>(C) Connector</b></p> <ol style="list-style-type: none"> <li>1) SMA</li> <li>2) FC</li> <li>3) ST</li> <li>4) Other _____</li> </ol>
<p><b>(D) Probe Diameter</b></p> <ol style="list-style-type: none"> <li>1) Ø0.125"</li> <li>2) Other _____</li> </ol>	<p><b>(E) Path Length*</b></p> <ol style="list-style-type: none"> <li>1) 2mm</li> <li>2) 5mm</li> <li>3) 10mm</li> <li>4) Other _____</li> </ol>	<p><i>*Double the gap measurement at "E" for path length.</i></p> <p><b>Specifying Method</b></p> <p>AM - <u>A</u> <u>B</u> <u>C</u> <u>D</u> <u>E</u> <u>X</u> <u>X</u> (PL-in)</p> <p>Example : AM-34111 06</p> <p>AM - <u>3</u> <u>4</u> <u>1</u> <u>1</u> <u>1</u> <u>0</u> <u>6</u> (in)</p> <p>Silica/Silica (VIS/NIR), 400 micron , SMA connector, Ø 0.125"probe diameter, 2mm path length, 6" probe length.</p> <p>Please contact RoMack regarding replaceable path length tips, or environmental concerns.</p>

Temperature Requirements: \_\_\_\_\_  
 Pressure Requirements: \_\_\_\_\_  
 Other Requirements: \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

# RoMack inc.

5583 Mooretown Road • Williamsburg, VA 23188

Phone: 757-258-4805

Fax: 757-258-4694

E-Mail: [contact@romackfiberoptics.com](mailto:contact@romackfiberoptics.com)